

Enjoy the Smart Surveillance!!

**PARAVIEW**  
CCTV SYSTEMS



LVD FC CE

**Features:**

- H.264 dual-stream video compression
- HDMI,VGA output and BNC output at the same time
- Plug and Play function
- Recording and playback are available in mobile phone
- All channels playback simultaneously
- 3G mobile phone and Email
- Support 20 visitors to remote checking
- Support 3 independent coding stream(local, network, mobile)

**Specifications:**

	Model No.	PARA- DV 1016P
system	operating system	embedded linux
	system resources	Simultaneous multi-channel real-time recording, playback, network operation , USB backup
Display	Interface	1 HDMI, 1 VGA, 1 BNC
	Resolution	monitor: D1, VGA, HDMI: 1920*1080
	Display Split	1/4/8/9/16
Record	video compression	H.264
	Resolution	NTSC:480fps@CIF PAL:400fps@CIF
	Record Rate	All channel@CIF (25/30fps)
	Record Mode	manual>alarm>motion detection>timing
	Record Interval	15~60min (default:60min);Pre-record:5sec;Alarm-record: 30~300sec
Playback&backup	Sync Playback	Multi-channel Simultaneously playback (1-16ch)
	Search Mode	Time/calendar/event/channel search
	Space Occupation	Video: CIF:4~5G/ day*channel D1: 8~10G/ day*channel audio: 691.2M/ day*channel
	Backup Mode	Network backup、USB
interface	video input	16ch BNC (1.0Vp-p,75Ω75Ω)
	video output	1ch BNC (1.0Vp-p,75Ω) , 1ch VGA, 1ch HDMI
	audio input	2ch RCA(200-2800mV,30KΩ)
	audio output	1ch RCA(200-3000mV,5KΩ)
	net interface	RJ45 10M/100M
	PTZ control	One RS485 port, support multiple PTZ protocols
	usb	2 USB2.0 ports (save two front interface)
	hard disk	1 SATA ports (4T at most per one)
others	Power supply	12V/3A
	Working Temperature	0℃-+55℃
	Working Humidity	10%—90%
	Atmospheric pressure	86kpa—106kpa
	dimension	255*225*45mm
	weight	1.5kg

**Design and specification are subjected to be changed without prior notice.**