

Enjoy the Smart Surveillance!!

**PARAVIEW**  
CCTV SYSTEMS



LVD FCC CE

#### Features:

- D1/CIF recording resolution available
- HDMI,VGA output and BNC output at the same time
- Plug and Play function
- Recording and playback are available in mobile phone
- All channels playback simultaneously
- 3G mobile phone and Email
- Support 20 visitors to remote checking
- Support 3 independent coding stream(local, network, mobile)

#### Specifications:

	Model No.	PARA- DV 104P
system	operating system	embedded linux
	system resources	Simultaneous multi-channel real-time recording, playback, network operation , USB backup
interface	user interface	support 16-bit true color graphical menu interface and mouse operation
Video	video compression	H.264
	display quality	monitor: D1 ; VGA、HDMI: 1920*1080
	play quality	D1/Half-D1/CIF/QCIF
	encode capacity	4ch D1 real-time
	decode capacity	4ch D1 real-time
	motion detect	Zones: 192 (16*12) detection zones,sensitivity: multi-level sensitivity (Only local channels)
Record&playback	record mode	manual>alarm>motion detection>timing
	local playback	Multi-channel Simultaneously playback
	search mode	Time/calendar/event/channel search
Storage&backup	record storage	HDD、network
	backup mode	Network backup、USB
interface	video input	4ch BNC (1.0Vp-p,75Ω)
	video output	1ch BNC (1.0Vp-p,75Ω) , 1ch VGA, 1ch HDMI
	audio input	4ch RCA(200-2800mV,30KΩ)
	audio output	1ch RCA(200-3000mV,5KΩ)
	net interface	RJ45 10M/100M
	PTZ control	One RS485 port, support multiple PTZ protocols
	usb	2 USB2.0 ports (save two front interface)
	hard disk	1 SATA ports (4T at most per one)
others	Power supply	12V/2.5A
	Working Temperature	0°C-+55°C
	Working Humidity	10%—90%
	Atmospheric pressure	86kpa—106kpa
	dimension	225*192*43mm
	weight	0.8kg

Design and specification are subjected to be changed without prior notice.