


4" PTZ Dome (Indoor)

	※ 360 Degree Continues Rotation
	※ Pan range: 0°~360° Continue
	※ Tilt range: 0°~90° Flip
	※ Pan Speed: Max 60°/sec
	※ Preset point: 32
	※ RS485 control
	※ Lens: Optional
	※ Size: \varnothing 125x210mm; Weight: 2.2kg

Model No.	EN-PT4-32X	EN-PT4-32
Internal camera	1/3 Sony 420TVL	1/3 Sony 420TVL
Lens	5-15mm varifocal lens (4-9mm Lens is optional)	8mm board lens
Power supply	DC12V 500mA	
Communication	RS485 (+/-)	
Protocol	Pelco-P/D	
Baudrate	1200/2400/4800/9600 bps	
Pan range	0°~360° Continue	
Tilt range	0°~90° Flip	
Pan Speed	Max 60°/sec	
Preset Point	32	
Auto Scan:	Yes (Programable speed and left right limited point)	
Home Position	Yes (Programable auto come back home position)	
Protection	IP66 for outdoor use	
Size	\varnothing 125x210mm	
Weight	2.2kg	

Model No.	EN-PTRC
	※ RS485
	※ Support Pelco P/D
	※ Baud Rate support 2100, 4800 and 9600
	※ Support 99 ID (Control 99pcs Cameras)
	※ Communication distance: Max.1200m
	※ With Led display
	※ Available for other Speed dome
	※ Weight 300g